



SPK1-AW560SP

TWO-WAY, ON-WALL, 2x30W ACTIVE SPEAKER PAIR WITH AUTO ON/OFF

The SPK1-AW560SP is a cost efficient on wall active speaker pair designed for a wide range of applications. The package includes two speakers, one passive and one active which power both speakers for a hassle-free installation. With a frequency range of 50Hz - 20kHz (-10dB) and a maximum SPL of 102dB (Peak 105dB), these speakers are well-suited for both speech and music applications in various facilities such as schools, meeting rooms, offices, or any other setting where high-quality sound from modern designed active speakers is required.

Furthermore, these speakers come equipped with an environmentally friendly auto-off function which ensures that the speakers enter standby mode after 5 minutes of inactivity, saving energy without interrupting your important meetings or conferences.

The package also includes U-brackets for easy mounting, but the speakers are also compatible with third-party mounting brackets, thanks to the inclusion of two M6 (73 mm wide standard) mounting holes.

Both balanced and unbalanced inputs are available, and the speakers remain completely silent even when an unbalanced cable is not connected to any audio source. Additional features of these speakers include loop out, sub out, two-band EQ, and volume control.

*When in AUTO mode the speaker goes to sleep after 5 minutes without signal

SPK1-AW560SP-WH (Front)



KEY FEATURES

- Powerful 5 1/4" polypropylene cone with rubber edge woofer
- 1" Titanium dome tweeter
- Waveguide 90°x90°
- 2 x 30W RMS; 2 x 60W continuous program
- Inputs: Line level on unbalanced RCA, 3.5mm and balanced terminal block
- Outputs: Loop line output and subwoofer output on 3.5mm
- Controls: Volume, bass and treble
- Power modes: ON/OFF/AUTO*
- Modern and stylish design
- U-bracket, 3m power cord (UK and EU), 3m 3.5mm TRS to 2 RCA and 4m speaker cable included
- Hole spacing for third party mounts (2 x M6, CC 73mm)

TIGHT POLICY

Faulty product - minimal down time.

Up until six months after purchase, TiGHT AV will replace your product in advance of return of faulty product.

Your investment - built to last.

This TiGHT AV product come with a one year limited warranty.



TiGHT
AV

SPECIFICATIONS

Built in power amplifier:	2 x 30W RMS; 2 x 60W continuous program
Frequency range:	50Hz to 20kHz @ -10dB
Frequency response:	90Hz to 20kHz @ ±3dB
Woofer:	5 1/4" polypropylene cone with rubber edge woofer
Tweeter	1" Titanium dome tweeter (Waveguide 90°x90°)
Sensitivity:	87dB SPL, 1W@1m for 1k Hz
Max spl:	Continuous: 102dB Peak: 105dB
Power source:	100-240V AC 50/60Hz
Crossover frequency:	2 kHz
Directivity factor (q):	4.0 averaged 1kHz to 10kHz @ 100 Degrees
Directivity index (di):	6.0dB averaged 1kHz to 10kHz @ 100 Degrees
Input connectors: (Summed when all is connected)	<ul style="list-style-type: none"> Line level unbalanced stereo audio on a 3.5mm TRS connector Line level balanced stereo audio on a terminal block connector Line level unbalanced stereo audio on left and right RCA connectors
Output connectors:	<ul style="list-style-type: none"> Speaker (to connect to the external passive speaker) 3.5mm mini jack lineout for optional sub-woofer 3.5mm mini jack Loop output
Damping factor:	>100 @ 8Ω/400Hz
S/n ratio:	> 83dB
Thd:	244 g
Controls:	Volume, bass and treble
Input power:	ON,OFF or AUTO
Power consumption:	0.3W (standby mode)
Inputs signal for system "wake-up" from standby mode:	≥10mV

Materials:	Aluminum grille, steel brackets, ABS cabinet
Weight per single speaker:	TBD
Weight with mounting kit:	TBD
Shipping weight (for pair):	7.2 kg
Dimensions (WxDxH):	19.2 cm x 18.5 cm x 28.5 cm (7.2" x 6.7" x 9.6")
Dimensions with mounting brackets (WxDxH):	19.2 cm x 23.5 cm x 28.8 cm (7.2" x 6.7" x 9.6")
Hole spacing third party mounting brackets:	c/c 73 mm using M6 bolts
Installation clearance (with mounting bracket):	Front panel to wall: 24 cm (9.5in) Back panel to wall: 4.5 cm (1.8in)
Included accessories:	<ul style="list-style-type: none"> 1 pair of U-shaped rotating mounting brackets 3 m (9.84ft) power cord 4 m (13.12ft) loudspeaker cable 3 m (9.84ft) 3.5mm to 2 RCA cable
Optional accessories:	Third party mounting brackets, fits for example K&M 24141
Colors:	Available in white or black
Compliance	CE
Environmental compliance	RoHS, WEEE

PACKAGE LIST

1x Active speaker
 1x Passive speaker
 2x U-Brackets*
 1x 3m (9.84ft) Power cord (UK)*
 1x 3m (9.84ft) Power cord (EU)*
 1x 4m (13.12ft) Loudspeaker cable*
 1x 3m (9.84ft) 3.5mm TRS to 2 RCA cable*

*White color accessories for SPK1-AW560SP-WH, black color accessories SPK1-AW560SP-BL

SPK1-AW560SP-WH (Back)



KEY FEATURES

- Powerful 5 1/4" polypropylene cone with rubber edge woofer
- 1" Titanium dome tweeter
- Waveguide 90°x90°
- 2 x 30W RMS; 2 x 60W continuous program
- Inputs: Line level on unbalanced RCA, 3.5mm and balanced terminal block
- Outputs: Loop line output and subwoofer output on 3.5mm
- Controls: Volume, bass and treble
- Power modes: ON/OFF/AUTO*
- Modern and stylish design
- U-bracket, 3m power cord (UK and EU), 3m 3,5mm TRS to 2 RCA and 4m speaker cable included
- Hole spacing for third party mounts (2 x M6, CC 73mm)

TIGHT POLICY



Faulty product - minimal down time.

Up until six months after purchase, TIGHT AV will replace your product in advance of return of faulty product.

Your investment - built to last.

This TIGHT AV product come with a one year limited warranty.

TIGHT
AV