



SPK1-C880T-WH

8" IN-CEILING SPEAKER WITH TRANSFORMER TAP AND WHITE MAGNETIC GRILLE


The SPK1-C650T-WH is a cost efficient in-ceiling speaker designed for a wide range of applications. With a frequency response of 50 Hz - 20 kHz (-10 dB) and a maximum SPL of 109 dB, it is well suited for speech and background music in facilities such as hotels, restaurants, retail stores and schools.

The speaker features a 8" polypropylene cone driver and a 0.75" Titanium pivoting dome tweeter. It supports both 8 Ohm and 70V/100V operations, with taps ranging from 1.3W to 15W.

A cardboard cutout template is included in the box, and spring clamp doglegs provide a quick and easy installation. The off-white magnetic grille is designed to blend in with common ceiling interior, giving the installation a discrete and sleek look.

With a weight of only 2.25 kg, the speaker can be directly mounted in ceiling tiles without risk of any visible sagging. Furthermore, the shallow profile of 111mm should make it a great fit in tight installations

SPL vs Freq



SPECIFICATIONS

GENERAL

RMS Power:	80W
Impedance:	8 Ω (in low-impedance setting)
Sensitivity(1m/1W):	90dB
Max SPL (1m):	109dB (low-impedance)*
Frequency Range (-10dB):	50Hz-20kHz
Woofer Type:	8" Polypropylene cone with rubber edge
Tweeter Type:	0.75"(13mm) Titanium pivoting dome tweeter
Crossover Slope:	12dB/Octave
Dimension:	Φ283x111mm
Cutout Size:	Φ258mm
Ceiling Thickness:	Dog-ears can support up to 30mm ceiling thickness
Net Weight:	2.25 kg
Grille:	Magnetic round grille
Color:	White
Transformer:	Knob Style, 70V : 1.3W-2.5W-5W-10W & 80, 100V : 2.5W-5W-10W-15W & 80
Safety Compliance:	CE
Environmental Compliance:	RoHS, WEEE
Warranty:	Limited 5 years warranty

* Half-space



TIGHT POLICY

Faulty product - minimal down time.

Up until six months after purchase, TIGHT AV will replace your product in advance of return of faulty product.

Your investment - built to last.

All TIGHT AV products come with a five year limited warranty.

TIGHT
AV